

PRODUCT DIMENSIONS

**EIGHT-CHANNEL
PIEZOELECTRIC SENSOR
CONNECTOR WITH MOLD ID**

PZ-8



SENSOR CABLE C/PZ-1645 ORDERING LENGTH

CABLE LENGTH		PART NO.
7.9"	0.2 m	C-PZ/1645-0.2
15.7"	0.4 m	C-PZ/1645-0.4
23.6"	0.6 m	C-PZ/1645-0.6
31.5"	0.8 m	C-PZ/1645-0.8
47.2"	1.2 m	C-PZ/1645-1.2
63.0"	1.6 m	C-PZ/1645-1.6
78.7"	2.0 m	C-PZ/1645-2.0

The eight-channel piezoelectric sensor connector with mold ID PZ-8 interfaces up to eight piezoelectric sensors with the RJG, Inc. eight-channel piezoelectric sensor adapter PZ/LX8F-S-ID and the eDART® or CoPilot® systems.

TECHNICAL SPECIFICATIONS

TEMPERATURES

Connector Temperature Maximum	392 °F	200 °C
Mold ID Temperature Maximum	257 °F	125 °C

CONNECTIONS

Sensor Cable Connectors	MCX Coaxial
Cable Connector	11-Pin Fischer



ADAPTER CABLE C-PZ/LX8F-S ORDERING LENGTH

CABLE LENGTH		PART NO.
19.7"	0.5 m	C-PZ/LX8F-S-.5M
39.4"	1.0 m	C-PZ/LX8F-S-1M
78.7"	2.0 m	C-PZ/LX8F-S-2M

INSTALLATION

Refer to product manual for all dimensions and installation specifications—available for download online at www.rjginc.com.

1 PZ-8—Eight-Channel Piezoelectric Connector

2 C-PZ/1645—Eight-Channel Piezoelectric Sensor Connector PZ-8 Cable

3 PZ/LX8F-S-ID—Eight-Channel Piezoelectric Sensor Adapter with Mold ID

4 C-PZ/LX8F-S—Eight-Channel Piezoelectric Sensor Adapter Cable

